

Point Orange Telemetry

Point Orange is a compact Logger/RTU device with integrated battery, a 3G modem with GPRS fallback, internal and/or external antenna, flexible I/O options, Modbus and SDI-12 master capability and a submersion sensor.

Point Orange provides real-time remote monitoring of up to 5 programmable sensors. It has software programmable I/O functionality for hundreds of configurable combinations and includes support for analogue, digital and counter inputs. The Point Orange can also communicate with third-party serial devices over Modbus (using RS232 and RS485) or SDI-12. In addition to the multiple configuration options the Point Orange offers local monitoring of battery voltage, cellular signal strength and ambient temperature.

The RTU offers a plug and play solution that minimises the need for additional site visits, with remote management functions including remote firmware upgrade enabling associated cost-savings. It can store thousands of records in memory for later retrieval by SCADA systems.

The Point Orange was designed from the outset as a self-contained, low cost fit-and-forget unit for use in harsh and hazardous environments in remote locations. Its design exploits mainstream technologies which help to minimise costs whilst at the same time ensuring reliability and a long product life. The latest developments in low power technology are used, allowing the Point Orange to derive all the power it needs (including sensor power, if required) from an internal lithium battery pack. This, together with an integral 3G modem, ensures a long service life with low infrastructure costs.



KEY FEATURES:

- Real-time remote monitoring of up to 5 sensors
- Software configurable I/O; supports AI, CI and DI
- Powers external current loop and active voltage sensors
- Tri-band 3G modem with quad band GSM/GPRS fallback with auto switching internal and external antenna
- Lithium battery with an expected life of 5+ years
- IP68 enclosure is submersible to 4 meters for 4 days
- Connects to Medina, DNP3 or WITS DNP3 Masters
- Can operate in isolation uploading data to a FTP server
- Modbus master communicating over RS232 and RS485
- SDI-12 interface for third party serial devices
- Remote firmware upgrade
- Remote configuration
- Patented integral submersion sensor
- Rich telemetry functionality including dynamic trending/logging and intelligent alarm reporting
- Flexible integrated installation bracket
- Automatic external power source detection
- ATEX compliant variant available - Point Blue

Technical Specification

Analogue Inputs	Up to 4 channels Type: Active current, passive current, active voltage, passive voltage Current range: 0-20mA, Voltage range: 0-2V Active AI power supply (12V DC, 80mA) Input impedance: 10.2k Ω Accuracy typically: $\pm 0.5\%$ (Max $\pm 2\%$) Absolute maximum ratings: $\pm 5\text{VDC}$ Resolution: 16-bits
Counter inputs	Up to 4 channels Volt free, Impedance: 50k Ω 32-bit counter support up to 100Hz
Digital inputs	Up to 5 channels Volt free, Impedance: 50k Ω
Power	Internal lithium battery pack Optional external battery pack DC power input (5-8V DC)
Protocols	Modbus DNP3 (Level 2+ elements of level 3 and 4) WITS DNP3 v1.1 Modbus master (RS232, RS485 full and half duplex) SDI-12 master
Memory	256MB flash memory and 512kB static RAM
Comms	Internal Tri-band 3G modem (850, 900, 2100 MHz) with quad band GPRS fallback (850, 900, 1800, 1900 MHz) Auto switching internal and external antenna
Local monitoring	Ambient temperature sensor ($\pm 1^\circ\text{C}$) Integrated submersion sensor Battery, loop, and external supply voltages ($\pm 2\%$) Automatic external power source detection and switching Antenna selection and performance
Remote management	Remote firmware upgrade Remote configuration
Dimensions	156mm \times 110mm \times 112mm (excluding mating cables) 0.6 Kg (fully assembled)
Environmental	Operating temperature -20°C to $+80^\circ\text{C}$ Relative Humidity up to 95% non-condensing Protection classification: IP68 4m for 4 days

